





INVESTOR IN PEOPLE

PRIORITY

The Patent Office Concept House Cardiff Road Newport South Wale **NP108Q**

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before reregistration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



The Patent **Office**



Request for grant of a patent (See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road Newport Gwent NP9 1RH

		LIVEVPURI	
1.	Your reference	11026P1GB/HC	
2.	**	0216556.1	5–1 N62903
3.	Full name, address and postcode of the or of each applicant (underline all surnames)	Reckitt Benckiser (UK) Limited / 7700 0.00- 103-105 Bath Road Slough Berkshire SL1 3UH UNITED KINGDOM	0216556.1
	Patents ADP number (if you know it)	07972136002	
	If the applicant is a corporate body, give the country/state of its incorporation	England	
4	Title of the invention	Dispenser	
5.	Name of your agent (if you have one)	John Crawford McKnight Reckitt Benckiser plc	
	"Address for service" in the United Kingdom	Group Patents Department	•
	to which all correspondence should be sent (including the postcode)	Dansom Lane HULL HU8 7DS UNITED KINGDOM	
	Patents ADP number (if you know it)	07799521001	
6.	If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number	Country Priority application number (if you know it)	Date of filing (day / month / year)
7.	If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application	Number of earlier application (day/month/year)	Date of filing (day / month / year)
8.	Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if: a) any applicant named in part 3 is not an inventor, or b) there is an inventor who is not named as an applicant, or —any named applicant is a corporate body.		
	See note (d))		

Patents Form 1/77

 Enter the number of sheets for any of the following items you are filing with this form.
 Do not count copies of the same document

Continuation sheets of this form

Description

6

Claim(s)

1

Abstract

1-12/16

Drawing(s)

1.4 1

10. If you are also filing any of the following, state how many against each item.

Priority documents
Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77)

One

Request for substantive examination

(Patents Form 10/77)

One

Any other documents (please specify)

FS2

11.

I/We request the grant of a patent on the basis of this application.

Signature

Date

John C McKnight

15 July 2002

2. Name and daytime telephone number of Person to contact in the United Kingdom

John C McKnight (01482) 583719

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- d) If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- e) Once you have filled in the form you must remember to sign and date it.
- f) For details of the fee and ways to pay please contact the Patents Office.

DISPENSER

The present invention relates to a portable device for dispensing a fragrance.

5

In everyday life we are subjected to offending olfactory sensations. For example, cooking smells, cigarette smoke and stale air when we are confined to closed environments, such as trains, cars and houses with limited air exchanging properties. Such strong smells are capable of causing a person to faint or to cause them considerable discomfort. Accordingly, occasions arise when a portable air freshening device would be desirable.

15

10 .

It is known to use smelling-bottles. These bottles are portable and contain smelling salts such as ammonium carbonate mixed with a scent to be sniffed as a restorative in faintness.

20

25

Furthermore, inhalers are known which comprise a stick with a vent at the extremity of the device and apertures around the base of the device. In use, the inhaler is inserted into the nostril of a user. The user then holds the other nostril closed and inhales deeply. The apertures at the base of the stick allow air flow through the inhaler which causes evaporation of a decongestant which is subsequently inhaled through the vent at the extremity of the stick.

30

Such devices are designed to deliver an intense amount of the inhaled product to the nasal passages and are therefore unsuitable for delivering certain fragrances.

35

Accordingly, the present invention provides a portable device for dispensing a fragrance comprising:

a housing containing a fragrance element; at least one aperture in a side of the housing in the vicinity of one end of the housing to release the fragrance from the housing;

and means to selectively open and close the aperture;

the one end being shaped to abut the lower end of a users nose such that in use the fragrance can be inhaled through the aperture to the nasal passage of a user.

The device of the present invention is advantageous over the prior art in that the relationship between the one end and the aperture is such that the aperture is close to, but not directly in contact with the users nose. Thus, the fragrance can be provided in a lower intensity whilst still guaranteeing local delivery to the user. This ensures that the fragrance does not affect people in the vicinity of the user.

20

25

30

35

15

5

10

Any composition which can release a pleasant smell and is suitable for use as a fragrance can be used in the present invention. Beyond the subjective enjoyment produced by pleasant fragrances, certain fragrances may produce psychological and physiological responses such as stress reduction due to activation of brain centres which are especially responsive to fragrances. In addition to fragrances, humans may enjoy and benefit from inhaling volatile substances which may not have a detectable scent, but which none-the less produce a distinct biological or psychological effect. These substances include, but are not limited to pheromones which may alter the sexual behaviour of humans, hormones which may alter the physiology of the body, mood altering substances, appetite-altering substances, organ extracts, plant extracts or other materials or chemicals which provide a desired

biological or psychological effect. The word "fragrance" in the context of the present invention encompasses all of the aforementioned substances.

- The fragrance element may be any fragrance in any form which is vaporizable at room temperature and atmospheric pressure. For example the fragrance element may be prepared as a gel or a paste to control spills or leaks. Furthermore, the fragrance element may be in liquid form and placed inside a reservoir. In a preferred embodiment a porous solid such as scintered PE or cellulose board is impregnated with the fragrance.
- 15 A fragrance element is placed in the enclosure formed by the housing. The fragrance element can be introduced into the enclosure at anytime during the assembly of the housing. In a preferred embodiment the fragrance element may have as a component of its design a form to assist in locations and attachment of the fastening element to the housing to secure it. For example one or more anchor pins, shafts or posts can be present.
- 25 Furthermore, in a preferred embodiment the device may have as part of its design sections of the housing which can be opened and/or removed to allow the user to replace and/or replenish the fragrance element so that the device can be used again.

The number of apertures present within the side of the housing in the vicinity of one end of the device is dependent upon the size of the device, the diameters of the apertures and the fragrance release rate required. Desirably the number of apertures is from 1 to 20, more preferably 5 to 15 and most preferably 10.

The average diameter of each aperture is preferably

- 4 -

from 1 mm to 7mm, more preferably from 1 to 4mm. The apertures of the device can have all the same diameter but in a preferred embodiment a plurality of apertures are present with varying diameters. The apertures may be arranged in an orderly or random pattern.

5

10

15

35

Any means can be used to selectively open and close the apertures. For example a stopper or a seal. In a preferred embodiment the means to selectively open and close the apertures is lid. The lid can be pivotally attached to the housing wherein the lid is movable from a closed position where the lid covers the aperture to seal the device to an open position where the aperture is uncovered. Desirably the lid is integrally hinged to the housing.

In a preferred embodiment the lid in its open position rests against the side of the housing adjacent to the aperture such that in use the lid prevents the aperture from the device from coming into contact with the top lip of the user.

In a preferred embodiment a catch is present which is positioned in the one end of the device to provide the user with a clear indication of the successful opening and closing of the lid by providing an audible "click". The "click" is provided by the interaction of the lid as it passes over the catch.

The one end of the device is arranged to abut the lower end of the nose. In a preferred embodiment the one end has a central recess to accommodate the septum of the user.

For a better understanding of the invention it will now be described, by way of example, with

reference to the accompanying drawings, in which:

Fig. 1 is a perspective view of the device with the lid open;

Fig. 2 is a perspective view of the device with the lid closed.

5

30

35

As shown in Figures 1 and 2 the device is in the shape of a flattened kidney bean. Such a shape enables the device to be held comfortably in the hand.

The device is typically about 70 mm long and about 45 mm across.

The housing 1 is made of plastic. The housing forms an inner enclosure 2 which contains the fragrance element 3.

The device further comprises a lid 4 which is pivotally attached to a side of the housing. The lid 4 is also made of plastic. The lid 4 is of such a shape that when the lid 4 is in its closed position it covers the apertures 5 to seal the device and is flush with the housing, as shown in Figure 2.

Furthermore, when the lid 4 is in its open position it can rest against the side of the housing, as shown in Figure 1, such that in use the lid 4 prevents the apertures 5 of the device coming into contact with the skin, and in particular the top lip of the user.

The section of the side of the housing which is covered by the lid 4 has a plurality of apertures 5 in the vicinity of the end 6 of the device. The apertures 5 are arranged in a random pattern. There are 11 apertures present. The diameters of the apertures 5 vary from 1.5 to 4 mm.

The end 6 of the device is arranged to abut the lower end of the nose. A first end region 7 is adapted to abut a first nasal passage and a second end region 8 is adapted to abut a second nasal passage with central recess 9, between the first and second end regions 7,8 to accommodate the septum.

As shown in Figure 1 there is a catch 10 positioned in the central recess 9 which holds the lid 4 in place when closed and provides an audible "click" when the lid 4 passes over the catch 10.

In use the user will open the lid 4 of the device,
which will be signified to the user by a "click" as
the lid passes over the catch 10, and then position
the end of the device 6 so that it abuts the lower end
of the nose.

As illustrated, the device of the present invention does not include powered means for dispensing the fragrance. Rather, the device utilizes air flow created by the user sniffing the housing 1 to promote a flow of air saturated with fragrance from the fragrance element 3 through the apertures 5 to the nasal passages of the user.

After use, the lid 4 will be shut, which is signified to the user by a "click" as the lid 4 passes over the catch 10, to ensure that the apertures 5 are covered and that the fragrance is selected within the device. This allows the air in the enclosure to become saturated with the fragrance.

5

CLAIMS

5

10

1. A portable device for dispensing a fragrance comprising:

a housing containing a fragrance element;

at least one aperture in a side of the housing in the vicinity of one end of the housing to release the fragrance from the housing;

and means to selectively open and close the aperture;

the one end being shaped to abut the lower end of a users nose such that in use the fragrance can be inhaled through the apertures to the nasal passage of the user.

2. A device as claimed in claim 1 further comprising a lid pivotally attached to the housing wherein the lid is movable from a closed position where the lid covers the aperture to seal the device to an open position where the aperture is uncovered.


- 3. A device as claimed in claim 2 wherein the lid in its open position rests against the side of the housing adjacent to the aperture such that in use the lid prevents the aperture of the device from coming into contact with the top lip of the user.
- 4. A device as claimed in claim 2 or 3 wherein the one end has a catch to provide an audible "click" as the lid passes over the catch.
 - 5. A device as claimed in any one of the preceding claims wherein the one end has a central recess to accommodate the septum of the user.


25

ABSTRACT

DISPENSER

A portable device for dispensing a fragrance comprising a housing 1 containing a fragrance element 3 and at least one aperture 5 in a side of the housing 1 in the vicinity of one end 6 of the housing to release the fragrance from the housing 1. A lid is attached to the housing 1 to selectively open and close the aperture 5. The one end 6 of the device is shaped to abut the lower end of a users nose such that in use the fragrance can be inhaled through the aperture 5 to the nasal passage of the user.





Ф.:.